

PHOENIX 27.5 CARBON				
Hardware				
NUMBER	PART NUMBER	DESCRIPTION	TORQUE	*
13	FP-RDH-TA-12MM-BLK-V3	Rear Derailleur Hanger 12mm TA		
14	FP-SCW-SCK-M5*10	M5x10 Rear Derailleur Hanger Screw	7 Nm (5 lb·ft)	G
15	FP-LNK-UL-43MM-V1-R1	43mm Offset Upper Link		
16	FP-BRG-6902-LLUMAXECN	28mm 6902 Ext'd Max-E Bearing		R
17	FP-LNK-LL-BLK-V7-R1	70mm Out-to-Out Lower Link		
18	FP-BRG-3903-LLUE	30mm 3903 Ext'd Lower Link Bearing		R
19	FP-CLV-109MM-V1-R1	109mm Clevis		
20	FP-PIN-CLV-M12*150-BLK-R1	M12 Clevis Shock Pin		G
21	FP-CLM-MECH-FRM-V1	Internal Routing Cable Clamp		
22	FP-SCW-FLT-M3*10	M3x10 Cable Clamp Screw (Included w/ Clamp)		
23	FP-BLT-M14*17-BLK-V1-R2	M14x17 Upper Link Bolt	35 Nm (27 lb·ft)	L
24	FP-BLT-M14*20-BLK-V2-R2	M14x20 Upper Link Clevis Bolt	35 Nm (27 lb·ft)	L
25	FP-BLT-M8*38-BLK-V2	M8x38 Front Shock Bolt	13 Nm (10 lb·ft)	G/L
26	FP-BLT-M16*22-BLK-V2-R2	M16x22 Lower Link Bolt	35 Nm (27 lb·ft)	L
27	FP-PRO-PHXCV2-HT-V1-R1	Phoenix Carbon 27.5 Headtube Guard		
28	FP-SCW-FLT-M3*15	M3x15 Headtube Guard Screw (Included w/ HT Guard)		
29	FP-PRO-PHXC-BMP-V1-R1	Phoenix Carbon 27.5 Bottom Out Bumper		
30	FP-SCW-FLT-M5*10	M5x10 Bottom-out Bumper Mounting Screw (Included w/ Bumper)		
31	FP-PRO-PHXC-V2-SS-V2-R1	Phoenix Carbon 27.5 Seatstay Guard		
32	FP-PRO-PHXC-V2-DT-V1-R1	Phoenix Carbon 27.5 Downtube Guard		
33	FP-PRO-PHXC-V2-CS-V2-R1	Phoenix Carbon 27.5 Chainstay Guard		
34	FP-PRO-PHXC-UR-V1-R1	Phoenix Carbon 27.5 Upright Guard		
35	FP-PLG-MECH-5.5MM	5.5mm Rubber Cable Plug		
36	FP-PRO-70MM-LL-V1-R1	70mm Lower Link Protector		
37	FRAME SIZE STICKER - XS/SM/MD/LG/XL	Frame Size Sticker		
Axles				
NUMBER	PART NUMBER	DESCRIPTION	TORQUE	*
101	157MM THROUGH AXLE V4	157mm DH Rear Axle	15 Nm (11 lb·ft)	G
102	-	12mm Axle Washer (Included w/ Axle)		
Bike Care				
*	PRODUCT TYPE	RECOMMENDED PRODUCT		
G	Grease	Motorex Bike Grease 2000		
L	Thread Locker**	Loctite Thread Locker #243 (or equivalent)		
G/L	Grease (Bolt Shaft) / Thread Locker (Bolt Threads)	See Above		
A	Anti-Seize	Motorex Copper Paste		
R	Retaining Compound	Loctite Retaining Compound #620 (or equivalent)		

**Threadlocker should always be applied to the corresponding female threads for the bolt specified

